

## Key Features

- Short Throw 92.7cm for 80" screen
- 2,000 ANSI lumens
- 4,000 hour Hybrid Filter
- Template function
- MyScreen
- Input source naming
- Transition Detector
- Audio pass Through
- Power saving mode
- Blackboard whiteboard mode
- Security Bar
- Quick on/Direct off



AMX Device Discovery



Screen size 4:3 Throw Distance

Diagonal*	Distance
60	68.3 cm
63	71.1 cm
70	80.5 cm
77	88.9 cm
80	92.7 cm
90	104.9 cm
100	117 cm

Throw Ratio: 0.6:1 (distance : width)

\*Measured in inches

## Specifications

Model Name	CP-D10 Series
Liquid Crystal Panel Structure	0.55" polysilicon active-matrix TFT x 3
Number of Pixels	786,432 pixels
Resolution	540 TV lines
Video	1024 dots X 768 lines
RGB	16.7 million colors
Colors	Native 4:3/16:9 compatible
Aspect Ratio	Digital Zoom x 1.3
Lens	0.6 (Fixed)
Throw Ratio (distance : width)	180W UHB
Lamp	2,000 ANSI Lumens
Brightness	Approximately 3,000 hours (normal) 4,000 hours (eco)
Expected lamp Life	400 : 1
Contrast Ratio	1W
Speaker Output	AC100 - 120V / AC220 - 240V 50/60 Hz
Power Supply	250W
Power Consumption	5°C - 35°C (41°F - 95°F)
Operating Temperature	5°C - 35°C (41°F - 95°F)
Input Signals	RGB
RGB	VGA, SVGA, XGA, WXGA, SXGA, SXGA+, UXGA, MAC 16"
Composite Video	NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N, PAL60
Component Video	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Acoustic Noise Level	37 dB (29 dB in Eco Mode)
H-Sync	15 kHz - 106 kHz
V-Sync	50 kHz - 120 kHz
Vertical Keystone	+ / - 5°
Approvals	UL, C-UL, FCC, CE, RoHS
RGB Input	Analog RGB
RGB Output	RGB
Video Input	S-Video
Composite Video	15pin Mini-Dsub x 2
Component Video	15pin Mini-Dsub x 1
Input	Mini DIN 4-pin connector x 1
Output	RCA jack x 1
Audio	Shared with VGA 15pin D-Sub
Input	Stereo Mini jack x 2, RCA(L/R) x 1 pair
Output	RCA(L/R) x 1 pair
Control Terminals	9-pin D-sub connector x 1 (RS-232 control)
Dimensions (W x D x H)	333 x 103 x 303 mm
Weight	3.5 kg
Additional Features	MyScreen, My Memory, My Button, My Text, My Source, Blackboard/ Whiteboard Mode, Day Time Mode, Input Source Naming(English), Resolution Setting, Template, Closed Caption, Audio Pass Through
Supplied Accessories	Remote Control, Batteries (AA), RGB cable, US Power Cord, Multiple language operator / Safety Manual, Security Label DT01091
Lamp	HL02483 (Optional RC-R008 with laser pointer)
Remote Control	UX35971
Filter	



Hitachi Australia Pty Ltd  
 Level 3, 82 Waterloo Road  
 North Ryde NSW 2113  
 Tel: +61 2 9888 4100  
 1800 HITACHI (Australia only)  
 Fax: +61 2 9888 4188  
 Email: dps@hitachi.com.au