



AMX Device Discovery



MyImage / Campus Notification System

Key Features

- Short throw 95.3cm for 88" screen
- Networking, control/ maintenance and security
- 2,000 ANSI lumens
- 4,000 hour hybrid filter
- Template function
- 10 watt speaker
- Input source naming
- Transition detector
- Audio pass through
- Power saving mode
- Blackboard whiteboard mode
- PJ Messenger



Specifications

| | | |
|--------------------------------|--|--|
| Model Name | CP-DW10N Series | |
| Liquid Crystal Panel Structure | 0.59" P-Si TFT x 3 | |
| Number of Pixels | 1,024,000 pixels | |
| Resolution | Video | 540 TV lines |
| | RGB | 1280 dots X 800 lines |
| Colors | 16.7 million colors | |
| Aspect Ratio | Native 16:10/4:3 compatible | |
| Lens | Digital Zoom x 1.3 | |
| Throw Ratio (distance : width) | 0.5 (Fixed) | |
| Lamp | 180W UHB | |
| Brightness | 2,000 ANSI Lumens | |
| Expected lamp Life | Approx. 3,000 hours(normal), 4,000 hours(Eco Mode) | |
| Contrast Ratio | 400 : 1 | |
| Speaker Output | 10W | |
| Power Supply | AC100 - 120V / AC220 - 240V 50/60 Hz | |
| Power Consumption | 250W | |
| Operating Temperature | 5°C - 35°C (41°F - 95°F) | |
| Input Signals | RGB | VGA, SVGA, XGA, WXGA, SXGA, SXGA+, UXGA, MAC 16" |
| | Composite Video | NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N, PAL60 |
| | Component Video | 480i, 480p, 576i, 576p, 720p, 1080i, 1080p |
| Acoustic Noise Level | 37 dB (29 dB in Eco Mode) | |
| H-Sync | 15 Hz - 106 Hz | |
| V-Sync | 50 Hz - 120 Hz | |
| Vertical Keystone | + / - 5° | |
| Approvals | UL, C-UL, FCC, CE, RoHS | |
| RGB Input | Analog RGB | 15pin Mini-Dsub x 2 |
| RGB Output | RGB | 15pin Mini-Dsub x 1 |
| Video Input | S-Video | Mini DIN 4-pin connector x 1 |
| | Composite Video | RCA jack x 1 |
| | Component Video | Shared with VGA 15pin D-Sub |
| Audio | Input | Stereo Mini jack x 2, RCA(L/R) x 1 pair |
| | Output | RCA(L/R) x 1 pair |
| Ethernet | RJ-45 | |
| Control Terminals | 9-pin D-sub connector x 1 (RS-232 control) | |
| Dimensions (W x D x H) | 333mm x 103mm x 303mm | |
| Weight | 3.7 kg | |
| Additional Features | MyScreen, My Memory, My Button, My Text, My Source, Blackboard/ Whiteboard Mode, Day Time Mode, Input Source Naming(English), Resolution Setting, Template, Closed Caption, Audio Pass Through, Network Bridge, Remote Control, Batteries (AA), RGB cable, US Power Cord, Multiple language operator / Safety Manual, Security Label DT01091 | |
| Supplied Accessories | HL02483 (Optional RC-R008 with laser pointer) UX35971 | |
| Lamp | HL02483 (Optional RC-R008 with laser pointer) | |
| Remote Control | UX35971 | |
| Filter | UX35971 | |

Screen Size 16:10 Throw Distance

| Diagonal* | Width* | Distance* |
|-----------|--------|-----------|
| 60 | 51 | 63.4cm |
| 63 | 53 | 66cm |
| 70 | 59 | 74.8cm |
| 77 | 65 | 83.3cm |
| 80 | 68 | 86.4cm |
| 90 | 76 | 96.5cm |
| 100 | 85 | 109.2cm |

Throw Ratio: 0.5:1 (distance : width)

*Measured in inches

