

 My Image / Campus Notification System  Closed Captioning

Key Features

- 2,000 ANSI Lumens
- Native XGA Resolution
- 4.1 lbs.
- 1 RGB Input / Composite / S-Video
- 802.11b/g Connect & Present with 4pc's wirelessly
- 1W speaker output
- Network Control, Maintenance & Security
- Lamp door on the top
- Approx. 3,000 hrs. (whisper Mode)
- 29 dB (Whisper Mode)
- Transition Detector
- PC-less presentation
- Template Function



Specifications

Model Name		CPX2 Series
Liquid Crystal Panel Structure		0.63" polysilicon active-matrix TFT x 3
Number of Pixels		786,432 pixels
Resolution	Video	540 TV lines
	RGB	1024 dots X 768 lines
Colors		16.7 million colors
Aspect Ratio		Native 4:3/16:9 compatible
Lens		F1.8 - 1.9, manual zoom x 1.2
Throw Ratio (distance : width)		1.3 - 1.5 : 1
Lamp		160W UHB
Brightness		2,000 ANSI Lumens
Expected lamp Life		Approximately 2,000 hours (normal) 3,000 hours (whisper)
Contrast Ratio		500 : 1
Speaker Output		1W (1 speaker)
Power Supply		AC100 - 120V / AC220 - 240V 50/60 Hz Power
Power Consumption		250W
Operating Temperature		5°C - 35°C (41°F - 95°F)
Input Signals	RGB	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, MAC13", MAC16"
	Composite Video	NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N
	Component Video	480i, 576i, 480p, 720p, 1080i
Acoustic Noise Level		35 dB (29 dB in whisper mode)
H-Sync		15 kHz - 106 kHz
V-Sync		50 kHz - 120 kHz
Vertical Keystone		+ / - 30°
Approvals		UL, C-UL, FCC, CE
RGB Input	Analog RGB	15-pin D-sub connector x 1
RGB Output	RGB	---
Video Input	S-Video	Mini DIN 4-pin connector x 1
	Composite Video	RCA jack x 1
	Component Video	Shared with VGA 15 pin D-Sub
Audio	Input	Stereo mini jack x 1
	Output	Stereo mini jack x 1
Control Terminals		USB Connector (USB Mouse) x 1
Other		SD Card, USB 2.0 Memory Reader
Wireless		Wireless 802.11 b/g
Ethernet		RJ-45 port / 100 base-T
Dimensions (W x D x H)		10.8" x 8.1" x 2.6"
Weight		4.1 lbs.
Additional Features		Kensington Slot, MyMemory / MyScreen / MyButtons, Digital Gamma Correction, Whiteboard/Blackboard Mode, Input Source Naming
Supplied Accessories		Remote Control, Batteries (AA), RGB cable, RCA Video Cable, US Power Cord, Multiple language operator / Safety Manual, Soft Case, Security Label, SD wireless card
Lamp		CPX1/253LAMP (DT00781)
Remote Control		HL02224
Filter		MU03602

Screen Size 4:3 Throw Distance

Diagonal*	Width*	Min*	Max*
30	24	30	36
60	48	61	73
80	64	81	97
100	80	102	122
120	96	122	147
150	120	153	183
200	160	204	245
300	240	306	368

Throw Ratio: 1.3 - 1.5:1 (distance : width)
*Measured in inches

