

 My Image / Campus Notification System  Closed Captioning

## Key Features

- 2,000 ANSI Lumens
- Native XGA Resolution
- 4.1 lbs.
- 1 RGB Input / Composite / S-Video
- 802.11b/g Connect & Present with 4pc's wirelessly
- 1W speaker output
- Network Control, Maintenance & Security
- Lamp door on the top
- Approx. 3,000 hrs. (whisper Mode)
- 29 dB (Whisper Mode)
- Transition Detector
- PC-less presentation
- Template Function



## Specifications

Model Name	CPX2 Series
Liquid Crystal Panel Structure	0.63" polysilicon active-matrix TFT x 3
Number of Pixels	786,432 pixels
Resolution	Video 540 TV lines 1024 dots X 768 lines RGB 16.7 million colors
Colors	16.7 million colors
Aspect Ratio	Native 4:3/16:9 compatible
Lens	F1.8 - 1.9, manual zoom x 1.2
Throw Ratio (distance : width)	1.3 - 1.5 : 1
Lamp	160W UHB
Brightness	2,000 ANSI Lumens
Expected lamp Life	Approximately 2,000 hours (normal) 3,000 hours (whisper)
Contrast Ratio	500 : 1
Speaker Output	1W (1 speaker)
Power Supply	AC100 - 120V / AC220 - 240V 50/60 Hz Power
Power Consumption	250W
Operating Temperature	5°C - 35°C (41°F - 95°F)
Input Signals	RGB Composite Video Component Video
Acoustic Noise Level	35 dB (29 dB in whisper mode)
H-Sync	15 kHz - 106 kHz
V-Sync	50 kHz - 120 kHz
Vertical Keystone	+ / - 30°
Approvals	UL, C-UL, FCC, CE
RGB Input	Analog RGB
RGB Output	RGB
Video Input	S-Video Composite Video Component Video
Audio	Input Output
Control Terminals	USB Connector (USB Mouse) x 1
Other	SD Card, USB 2.0 Memory Reader
Wireless	Wireless 802.11 b/g
Ethernet	RJ-45 port / 100 base-T
Dimensions (W x D x H)	10.8" x 8.1" x 2.6"
Weight	4.1 lbs.
Additional Features	Kensington Slot, MyMemory / MyScreen / MyButtons, Digital Gamma Correction, Whiteboard/Blackboard Mode, Input Source Naming
Supplied Accessories	Remote Control, Batteries (AA), RGB cable, RCA Video Cable, US Power Cord, Multiple language operator / Safety Manual, Soft Case, Security Label, SD wireless card
Lamp	CPX1/2/53LAMP (DT00781)
Remote Control	HL02224
Filter	MU03602

Screen Size 4:3    Throw Distance

Diagonal*	Width*	Min*	Max*
30	24	30	36
60	48	61	73
80	64	81	97
100	80	102	122
120	96	122	147
150	120	153	183
200	160	204	245
300	240	306	368

Throw Ratio: 1.3 - 1.5:1 (distance : width)  
\*Measured in inches

