



Compatible

HDMI™
HIGH-DEFINITION MULTIMEDIA INTERFACE

1920x1080
FULL HD



INTERACTIVE

75" Interactive Flat Panel Display



/hitachiDPSAustralia



@HitachiAU_DPS

HITACHI
Inspire the Next

Technical Specifications



LCD Component	75" TFT LCD [74.54 inches (189.3 cm) diagonal]
Backlight	LED Backlight
Max. Resolution	1920 x 1080
Max. Colours	16.7 million colours
Brightness	400 cd/m2
Contrast Ratio	5000:1
Viewing Angle (H/V)	178° / 178°
Video Colour System	480i, 480P, 576P, 720P, 1080i, 1080P
Signal (Analog)	VGA, SVGA, XGA, WXGA, FULL-HD
Panel Life Time	Up to 30000 hours
Frequency	120Hz
Touch Screen	Infrared Touch Screen 10 points support
Glass	Anti Glare
Input Terminals (Front)	USB A x 1, USB B x 1, HDMI x 1
Input Terminals (Rear)	Digital HDMI x 2 supporting HDCP decoding. HDMI 2 - shared with front terminal, Display port x 1 Analog Audio Control (RS-232C) USB Type B
Output Terminals	Line out (3.5mm mini jack) x 1 For External Speaker Total 20W speaker support
OSD (Support 16 languages)	English + 15 others
Screen Freeze	Screen Freeze Capability
Speaker	10W + 10W
TouchPanel	Detection Method Infrared blocking detection method Detection Area 1650.24mm (W) x 928.26mm (H) Touch Accuracy ±2mm (over 90% Area) PC Connector USB 2.0 Driver Win7/8 32/64bits & Mac OS drivers for touch screen calibration Touch Pen Passive stylus, finger or any IR opaque object.
Power Requirement	100-240V AC, 50/60Hz, 4 A
Operating/Storage Temperature	Operating temperature: 0 - 40 degrees Celsius; Storage temperature: -20 to 60 degrees Celsius
Operating/Storage Humidity	Operating Humidity: 90% relative humidity non-condensing
Power Consumption Operating/Standby	Max 333W / 1W
Dimensions (mm)	1,765 x 1,052 x 99
Weight	84kg
Colour	Black Bezel
Main Accessories	Power Cable, Remote Controller and Battery, USB cable (5M), HDMI Cable (5M), Stylus Pen x 2, Driver DVD
Certification	RoHS, CB, S-Mark, RCM

