

## Accessories and Lenses

<b>Supplied Accessories</b>	Remote control, power cord, computer cable, AA batteries x2, lens cover, adapter cover, security label, user's manual CD, user's manual, application CD
<b>Optional Accessories</b>	Wireless adapter (USBWL11N), Wired remote HL03131
<b>Replacement Parts</b>	
<b>Lamp</b>	DT01931
<b>Remote Control</b>	HL03037
<b>Filter</b>	UX41161

## Projection Throw Chart (In Meters and Inches)

Screen Size 16:10      Throw Distance

Diagonal	Width	Min	Max
0.76m (30")	0.64m (25")	0.84m (33")	1.47m (58")
1.52m (60")	1.30m (51")	1.73m (68")	3.00m (118")
2.03m (80")	1.73m (68")	2.31m (91")	4.01m (158")
2.54m (100")	2.16m (85")	2.92m (115")	5.03m (198")
5.08m (200")	4.32m (170")	5.87m (231")	10.08m (397")
7.62m (300")	6.45m (254")	8.84m (348")	15.16m (597")

Throw Ratio: 1.4 - 2.3 : 1 (distance : width)

## Specifications

Display	<b>Projection Technology</b>	3LCD, 3 chip technology
	<b>Resolution</b>	WUXGA 1920 x 1200
	<b>White Light Output</b>	5,200 ANSI lumens
	<b>Color Light Output</b>	5,200 ANSI lumens
	<b>Colors</b>	16.7 million colors
	<b>Aspect Ratio</b>	Native 16:10 / 4:3, 14:9 and 16:9 compatible
	<b>Contrast Ratio</b>	10000 : 1 (using active IRIS)
Lens & Operation	<b>Throw Ratio</b> (distance : width)	1.4 - 2.3 : 1
	<b>Focus Distance</b>	33" - 597"
	<b>Display Size</b>	30" - 300"
	<b>Lens</b>	F = 1.58 - 2.06, x 1.7 manual zoom, focus & lens shift
	<b>Lamp Wattage</b>	300W
	<b>Expected Lamp Life*</b>	Approximately 4,000 hours (standard mode) 6,000 hours (Eco mode)
	<b>Expected Filter Life**</b>	Approximately 10,000 hours
Compatibility	<b>Speaker Output</b>	16W
	<b>Keystone</b>	H and V: +/- 30°
	<b>Computer</b>	VGA, SVGA, XGA, WXGA, WXGA+/SXGA/SXGA+/WSXGA+/UXGA/WUXGA, MAC 16"
	<b>H-Sync</b>	15 kHz - 106 kHz
	<b>V-Sync</b>	50 Hz - 120 Hz
	<b>Composite Video</b>	NTSC, NTSC4.43, PAL, PAL-M, -N, SECAM
	<b>Component Video</b>	480i, 480p, 576i, 720p, 1080i, 1080p
Connectors	<b>HDMI</b>	480i, 480p, 576i, 720p, 1080i, 1080p, Computer signal TMDS clock 27 MHz - 150 MHz
	<b>Digital Input</b>	HDMI x 2, HDBaseT x 1
	<b>HDMI Output</b>	HDMI x 1
	<b>Computer Input 1</b>	15-pin mini D-sub x 1
	<b>Computer Monitor Output</b>	15-pin mini D-sub x 1, HDMI x 1
	<b>Video Input</b>	
	S-Video	N/A
	Composite Video	RCA jack x 1
	Component Video	15-pin mini D-sub x 1 (shared with computer input)
	<b>Audio Input</b>	3.5 mm stereo mini jack x 1, RCA jack (L/R) x 1
	<b>Audio Output</b>	3.5 mm stereo mini jack x 1
	<b>Network LAN Wired</b>	RJ-45 port (10 base-T / 100 base-TX)
	<b>Network LAN Wireless</b>	USB-A, IEEE802.11 b/g/n - optional wireless adapter required
Ratings & Warranty	<b>HDBaseT</b>	RJ-45 port x 1
	<b>USB</b>	Type A x 1 (wireless network)
	<b>Control Terminals</b>	9-pin D-sub x 1 (RS-232 control)
	<b>Power Supply</b>	AC 100-120V/220-240V, 50/60Hz
	<b>Power Consumption</b>	440W / 420W
	<b>Operating Temperature</b>	Normal mode : 0-35°C, Eco mode : 0-40°C
	<b>Dimensions (W x D x H)</b>	460x334x138mm (excluding protruding parts)
<b>Weight</b>	Approximately 7.1kg	
<b>Approvals</b>	RCM class A (AU/ NZ), UL New Zealand (AU/ NZ)	
<b>Warranty</b>	3 year limited parts and labor	

\* Actual lamp life will vary by individual lamp and based on environmental conditions, selected operating mode, user settings and usage. Hours of average lamp life specified are not guaranteed and do not constitute part of the product or lamp warranty. Lamp brightness decreases over time.

\*\* Actual filter life will vary by individual filter and based on environmental conditions, selected operating mode, user settings and usage. Hours of average filter life specified are not guaranteed and do not constitute part of the product warranty.



HI0450-03/16-Rev.3

All specifications subject to change without notice.  
3LCD and the 3LCD logo are registered trademarks of the Seiko Epson Corporation.  
iPad and iPhone are registered trademarks of Apple Inc., registered in the U.S. and other countries.  
©2016 Hitachi America, Ltd. All Rights Reserved.



Hitachi Australia Pty. Ltd.

Toll Free: 1800 HITACHI • Email: dps@hitachi.com.au

Web: www.hitachi.com.au/dps

