

MODEL	L42X01AU	L37X01AU	L32H01AU	L26H01AU
<b>PICTURE</b>				
Aspect Ratio	16 : 9	16 : 9	16 : 9	16 : 9
Number of Pixels (HxV)	1920 x 1080 (2,073,600)	1920 x 1080 (2,073,600)	1366 x 768 (1,049,088)	1366 x 768 (1,049,088)
Panel Type	Full HD Progressive Scan	Full HD Progressive Scan	HD Progressive Scan	HD Progressive Scan
Screen Size (diagonal) mm	1,067	940	800	661
Contrast Ratio	10,000:1 Dynamic	10,000:1 Dynamic	10,000:1 Dynamic	10,000:1 Dynamic
Panel Response Time	5ms	6ms	6ms	6ms
<b>TUNER</b>				
DVB High Definition Tuner Integrated	Yes	Yes	Yes	Yes
Analogue Tuner Integrated	Yes	Yes	Yes	Yes
Analogue RF Reception	(NTSC-M) (SECAM B/G/D/K1) (PAL B,G,H/I/D,K)	(NTSC-M) (SECAM B/G/D/K1) (PAL B,G,H/I/D,K)	(NTSC-M) (SECAM B/G/D,K/K1) (PAL B,G,H/I/D,K)	(NTSC-M) (SECAM B/G/D,K/K1) (PAL B,G,H/I/D,K)
Analogue RF Audio Reception	A2/NICAM	A2/NICAM	A2/NICAM	A2/NICAM
<b>VIDEO FORMATS</b>				
Video Signal	PAL, SECAM, NTSC3.58, NTSC4.43, PAL60, N-PAL, M-PAL	PAL, SECAM, NTSC3.58, NTSC4.43, PAL60, N-PAL, M-PAL	PAL, SECAM, NTSC3.58, NTSC4.43, PAL60, N-PAL, M-PAL	PAL, SECAM, NTSC3.58, NTSC4.43, PAL60, N-PAL, M-PAL
Component Signal	480i/p, 576i/p, 720p(50/60), 1080i(50/60), 1080p(50/60/24)	480i/p, 576i/p, 720p(50/60), 1080i(50/60), 1080p(50/60/24)	480i/p, 576i/p, 720p(50/60), 1080i(50/60), 1080p(50/60/24)	480i/p, 576i/p, 720p(50/60), 1080i(50/60), 1080p(50/60/24)
HDMI Signal (video mode)	480i/p, 576i/p, 720p(50/60), 1080i(50/60), 1080p(50/60/24) VGA	480i/p, 576i/p, 720p(50/60), 1080i(50/60), 1080p(50/60/24) VGA	480i/p, 576i/p, 720p(50/60), 1080i(50/60), 1080p(50/60/24), VGA	480i/p, 576i/p, 720p(50/60), 1080i(50/60), 1080p(50/60/24), VGA
Analogue RGB Signal	VGA - WXGA (1360 x 768 @ 60Hz)	VGA - WXGA (1360 x 768 @ 60Hz)	VGA - WXGA (1360 x 768 @ 60Hz)	VGA - WXGA (1360 x 768 @ 60Hz)
<b>INPUTS &amp; OUTPUTS</b>				
Total Number of Connectable Sources	8	8	6	6
<b>VIDEO CONNECTION CONFIGURATIONS</b>				
Composite Video with Analogue Audio (RCA)	2 (1 rear 1 side)	2 (1 rear 1 side)	2 (1 rear 1 side)	2 (1 rear 1 side)
S Video with Analogue Audio (RCA)	2 (1 rear 1 side)	1	1	1
Component Video with Analogue Audio (RCA)	2	2	2	2
HDMI Input	3 (2 rear 1 side)	3 (2 rear 1 side)	1	1
Stereo Analogue Audio for RGB	1 (3.5mm mini jack)	1 (3.5mm mini jack)	1 (3.5mm mini jack)	1 (3.5mm mini jack)

MODEL	L42X01AU	L37X01AU	L32H01AU	L26H01AU
<b>OTHER CONNECTIONS</b>				
RGB Input (PC)	RGB : Mini D-sub 15P	RGB : Mini D-sub 15P	RGB : Mini D-sub 15P	RGB : Mini D-sub 15P
Headphone Socket (3.5mm)	Yes	Yes	Yes	Yes
A/V Output	1x Composite Video with Analogue audio (RCA)	1x Composite Video with Analogue audio (RCA)	1x Composite Video with Analogue audio (RCA)	1x Composite Video with Analogue audio (RCA)
Digital Audio Out	Yes	Yes	Yes	Yes
<b>SOUND</b>				
Surround Sound	Matrix Surround	Matrix Surround	Matrix Surround	Matrix Surround
Automatic Volume Level	Yes (Perfect Volume)	Yes (Perfect Volume)	Yes (Perfect Volume)	Yes (Perfect Volume)
Sound Modes	4 Mode	4 Mode	4 Mode	4 Mode
<b>PICTURE ASPECT MODES</b>				
TV/Video (input signal dependent)	4:3, Panoramic, Cinema, Full	4:3, Panoramic, Cinema, Full	4:3, Panoramic, Cinema, Full	4:3, Panoramic, Cinema, Full
PC	4:3, Full	4:3, Full	4:3, Full	4:3, Full
<b>OTHER FUNCTIONS</b>				
Timer	On / Off	On / Off	On / Off	On / Off
Multi Picture Function	Yes	Yes	Yes	Yes
Analogue Teletext	1000 Page	1000 Page	1000 Page	1000 Page
Swivel Base	Manual	Manual	Manual	Fixed
<b>REMOTE CONTROL FUNCTIONS</b>				
One Touch Input Switching	Yes	Yes	Yes	Yes
<b>GENERAL</b>				
Dimensions excluding Stand (WxHxD)mm	1033 x 692 x 126	910 x 627 x 125	790 x 550 x 122	663 x 470 x 124
Dimensions including Stand (WxHxD)mm	1033 x 749 x 365	910 x 680 x 365	790 x 602 x 365	663 x 509 x 262
Weight excluding Stand (kg)	24.2	20.1	16	12.4
Weight including Stand (kg)	28.5	24.4	20.1	13
Power Supply	AC110V-240V (50/60Hz)	AC110V-240V (50/60Hz)	AC110V-240V (50/60Hz)	AC110V-240V (50/60Hz)
Power Consumption	210W	177W	144W	105W
Power Consumption Standby Mode	<2W	<2W	<2W	<2W

† Terminal layouts are for illustration purposes only and are not to scale. Refer to the user manual or your Hitachi dealer for exact layout.