HITFHD6516 / HITFHD6516PC




Technical Specifications









LCD Component		65" TFT LCD [64.5 inches (163.8 cm) diagonal]
Backlight		Edge LED Backlight
Max. Resolution		1920 x 1080
Max. Colours		1.07 billion colours
Brightness Contrast Ratio		360 cd/m2 4000:1
Viewing Angle (H/V)		178° /178°
Video Colour System		480i,480P,576P,720P,1080i/30,1080i/50, 1080P/24,
Signal (Analog)		VGA.SVGA.XGA.WXGA.FULL-HD
Panel Life Time		30000 hours
Frequency		60Hz
Touch Screen		Infrared Touch Screen 6 points support
Glass		Anti Glare
Input Terminals		
,	Digital	HDMI x 2 supporting HDCP decoding.
	Analog	VGA x 1 D-Sub 15 pin.
	PLUG & PLAY	DDC2B (VESA) for Computer HDMI-1,VGA
	Audio	Microphone mini 3.5mm jack x 1, Line out 3.5mm x 1
	Control (RS-232C)	D-Sub 9pin x1 for device control
	USB Type A	USB x 1 (for external usage of Touch screen)
Output Terminals		
	Audio	Line out (3.5mm mini jack) x 1
	Control (RS-232C)	D-sub 9 pin x 1
	For External Speaker	Total 20W speaker support
OSD		Independent from languages, the OSD is iconic
Screen Freeze		Screen Freeze Capability
Speaker		15W + 15W
TouchPanel	Data attau Matta at	1.6 111 12 11 12 11 10544 41 1 0540 01 1
	Detection Method	Infrared blocking detection method, 6514 – 4 touch, 6516 – 6 touch
	Detection Area	1428.48mm (H) x 803.52mm (V)
	Touch Accuracy PC Connector	±2mm(over 90% Area) USB 2.0
	Driver	Win7/8 32/64bits OS inbox driver and driver for touch screen calibration
	Touch Pen	Passive stylus, finger or any IR opaque object.
Power Requirement	TOUGHT 611	220V ~50Hz 1.2 A
		Operating temperature: 0 - 50 degrees Celcius Storage temperature:
Operating/Storage Temperature		-15 to 50 degrees Celcius
Operating/Storage Humidity		Operating Humidity: 90% relative humidity non-condensing
Power Consumption Operating/Standby		270W / 1W
Dimensions (mm)		1,562 x 93 x 960
Weight		57kg, 125.6lbs
Colour		White Bezel
Main Accessories		Power Cable (1450mm), IB, Remote Controller and Battery (CR2025 3V),
Main Accessories		HDMI Cable (1500mm), Dipole Wi-Fi antenna, Stylus Pen, Driver DVD
Remote Control		Protocol: NEC6122
		Carrier Frequency: 37.92KHz
Certification		RoHs, CB, S-Mark
DC Consideration LITE	UD6516DC only	
PC Specification HITFHD6516PC only Processor		Intel I3 2.10GHz
Operating System		Windows 8.1 Pro 64-bit
Chipset		Sandy Bridge Mobile CPU
System Memory		4GB RAM, 500GB HDD
Network		
	WLAN	802.11 a/b/g/n Dual Band 2.4GHz-5GHz with MIMO support.
	Bluetooth	Bluetooth 4.0
	LAN:	10/100/1000 Mbps LAN support
USB		3.0 USB x2, 2.0 USB x2