

HITACHI

Inspire the Next[®]

CP-A100 Projector

SPECIFICATIONS

Model name	CP-A100	
Liquid crystal panel	0.63" polysilicon active-matrix TFT x 3	
Number of pixels	786,432 pixels (V768 x H1,024)	
Resolution	1,024 x 768 color pixels	
Projection method	Mirror type	
Lens	Fixed lens, power focus	
Lamp	220W UHB	
Brightness	2,500 Lumens	
Contrast ratio	400:1	
Audio	7W mono	
Keystone correction	Manual Vertical Keystone	
Power supply	AC100-120V/AC220-240V	
Operating temperature	5-35°C (41-95°F)	
Input signals	Computer input	VGA, SVGA, XGA, SXGA, UXGA, MAC16"
	Video input	NTSC, NTSC4.43, PAL, SECAM, M-PAL, N-PAL HDTV: 750p (720p), 1125i (1080i) SDTV: 525i (480i), 525p (480p), 625i (576i)
Input/output terminals	Video input	S-Video: Jack x 1, Composite video: RCA jack x 1, Component video: RCA jack x 3
	Audio input	Stereo Mini jack x 2, RCA jack x 2 (L/R)
	Computer input	Analog RGB: 15-pin Mini-Dsub x 2
	Audio output	Stereo Mini jack x 1
	Monitor output	Analog RGB: 15-pin Mini -Dsub x 1
	Control and mouse	9-pin Dsub x 1 for RS232C, USB type B x 1 for mouse control
	Wired network	RJ-45 x 1
Agency certifications	UL60950-1/C-UL, FCC Part15 class B, AS/NZS CISPR22 class B, CE	
Dimensions (WxHxD)	397 x 131 x 356mm (15.63" x 5.16" x 14.02") [excl. protruding part, when mirror is closed.] 486 x 131 x 356mm (19.13" x 5.16" x 14.02") [excl. protruding part, when cable cover is attached.]	
Weight	5.8kg (12.8 lbs.)	
Standard accessories	Computer cable, Remote control, Batteries, Power cord, User's manual, Security label, Cable cover	
Optional accessories	Soft case (CA100), Tabletop use kit (TT100)	