

Accessories	
<b>Supplied Accessories</b>	Remote control, power cord, computer cable, USB cable, interactive software DVD, interactive pen x 2, pen tips x 4, user's manual
<b>Optional Accessories</b>	Interactive pen (I-PEN3), interactive pen tip UX40381, finger touch unit (FT-01), wall mount (HAS-WM05), table stand kit (TT03), bracket for Apple TV (HAS-RB01), wireless adapter (USBWL11N)
Replacement Parts	
<b>Lamp</b>	DT01411 with filter
<b>Remote Control</b>	HL03033
<b>Filter</b>	UX37191

## Projection Throw Chart (In meters and inches)

Screen Size	Throw Distance		
	Diagonal	Distance from edge of projector to screen	Distance from mirror cover to screen
16:10	1.52m (60")	0.13m (5.0")	0.41m (16.1")
	1.78m (70")	0.20m (7.8")	0.48m (18.9")
	2.03m (80")	0.27m (10.5")	0.55m (21.6")
	2.29m (90")	0.34m (13.3")	0.62m (24.4")
	2.54m (100")	0.41m (16.1")	0.69m (27.1")

Throw Ratio: (distance : width)  
0.2 : 1 from edge of projector  
0.3 : 1 from mirror cover



- Comes bundled with Hitachi interactive projectors
- World-class integrated software
- Collaborate, integrate, annotate

Specifications		
Display	<b>Projection Technology</b>	3LCD, 3 chip technology
	<b>Resolution</b>	WXGA 1280 x 800
	<b>White Light Output</b>	3,300 ANSI lumens
	<b>Color Light Output</b>	3,300 ANSI lumens
	<b>Colors</b>	16.7 million colors
	<b>Aspect Ratio</b>	Native 16:10 / 4:3 and 16:9 compatible
	<b>Contrast Ratio</b>	10000 : 1 (using active IRIS)
Lens & Operation	<b>Throw Ratio</b> (distance : width)	0.2 : 1 from edge of projector to screen 0.3 : 1 from mirror cover to screen
	<b>Focus Distance</b>	16" - 27" from mirror cover to screen
	<b>Display Size</b>	60" - 100"
	<b>Lens</b>	F = 1.8, f = 4.21 mm
	<b>Lamp Wattage</b>	250W
Compatibility	<b>Expected Lamp Life*</b>	Approximately 4,000 hours (standard mode) 6,000 hours (Eco mode)
	<b>Expected Filter Life**</b>	Approximately 4,000 hours
	<b>Speaker Output</b>	16W
	<b>Keystone</b>	H and V: +/- 5°
Connectors	<b>Computer</b>	VGA, SVGA, XGA, WXGA, WXGA+/SXGA/WSXGA+/UXGA (compressed), MAC 16"
	<b>H-Sync</b>	15 kHz - 106 kHz
	<b>V-Sync</b>	50 Hz - 120 Hz
	<b>Composite Video</b>	NTSC, NTSC4.43, PAL, PAL-M, -N, SECAM
	<b>Component Video</b>	480i, 480p, 576i, 720p, 1080i, 1080p
	<b>HDMI</b>	480i, 480p, 576i, 720p, 1080i, 1080p, computer signal TMDS clock 27 MHz - 150 MHz
	<b>USB Connection***</b>	USB 2.0
	<b>Digital Input</b>	HDMI x 2 (HDCP compliant)
	<b>Computer Input 1</b>	15-pin mini D-sub x 1
	<b>Computer Input 2</b>	15-pin mini D-sub x 1
Ratings & Warranty	<b>Computer Monitor Output</b>	15-pin mini D-sub x 1 (shared with computer in 2)
	<b>Video Input</b>	
	S-Video	N/A
	Composite Video	RCA jack x 1
	Component Video	15-pin D-sub x 2 (shared with computer in 1/2)
	<b>Audio Input</b>	3.5 mm stereo mini jack x 1, RCA jack (L/R) x 1, MIC-in 3.5 mm mini jack x 1
	<b>Audio Output</b>	3.5 mm stereo mini jack x 1
	<b>Network LAN Wired</b>	RJ-45 port (10 base-T / 100 base-TX)
	<b>Network LAN Wireless</b>	USB-A, IEEE802.11 b/g/n - optional wireless adapter required
	<b>USB</b>	Type A x 2 (PC-less presentation, wireless adapter) Type B x 1 (USB display or mouse control)
Ratings & Warranty	<b>Control Terminals</b>	9-pin D-sub x 1 (RS-232 control)
	<b>Power Supply</b>	AC100-120V / AC220-240V, 50/60Hz
	<b>Power Consumption</b>	360W
	<b>Operating Temperature</b>	0°C - 40°C
	<b>Dimensions (W x D x H)</b>	376 x 361 x 137mm (excluding protruding parts)
	<b>Weight</b>	Approximately 4.49 kg
	<b>Approvals</b>	RCM class A (AU/ NZ), UL New Zealand (AU/ NZ)
<b>Warranty</b>	3 year limited parts and labor	

\* Actual lamp life will vary by individual lamp based on environmental conditions, selected operating mode, user settings and usage. Hours of average lamp life specified are not guaranteed and do not constitute part of the product or lamp warranty. Lamp brightness decreases over time.

\*\* Actual filter life will vary by individual filter based on environmental conditions, selected operating mode, user settings and usage. Hours of average filter life specified are not guaranteed and do not constitute part of the product warranty.

\*\*\* If you need a USB connection longer than 15 feet, please use a "USB Active cable" which supports USB 2.0 or later. If you need to use a USB HUB between the PC and Projector, no more than one is recommended.

HI0422-Rev.3-08/15  
All specifications subject to change without notice.  
3LCD and the 3LCD logo are registered trademarks of the Seiko Epson Corporation.  
©2015 Hitachi America, Ltd. All Rights Reserved.

### Hitachi Australia Pty. Ltd.

Toll Free: 1800 HITACHI • Email: dps@hitachi.com.au  
Web: www.hitachi.com.au/dps

