


Ultra Short Throw LCD Projectors


Specifications							
Model name	CP-TW3005	CP-TW2505	CP-AW3005	CP-AW2505	CP-AX3505	CP-AX3005	CP-AX2505
Display system	3LCD						
Display device	Size of effective display area	0.59", aspect ratio 16 : 10			0.63", aspect ratio 4 : 3		
	Number of pixels	1,024,000 pixels (1280 horizontal x 800 vertical)			786,432 pixels (1024 horizontal x 768 vertical)		
Lens	Zoom	Digital zoom: x 1.35					
	Focus	Powered					
Light source	250W	225W	250W	225W	250W	225W	
Screen size	60 - 100 inch						
Light output(Brightness)	3,300lm	2,700lm	3,300lm	2,700lm	3,600lm	3,300lm	2,700lm
Contrast ratio	10,000 : 1 (PRESENTATION mode)						
Speaker	16W x 1 mono						
Displayable scanning frequency	Horizontal	15 - 106 kHz					
	Vertical	50 - 120 Hz					
Terminals	COMPUTER IN 1	Mini-D-sub 15-pin connector x 1					
	COMPUTER IN 2 / MONITOR OUT	Mini-D-sub 15-pin connector x 1					
VIDEO	Composite video (RCA connector) x 1						
HDMI IN	HDMI connector x 2 (HDCP compliant)						
MHL IN	HDMI connector x 1 (HDCP compliant)	-					
AUDIO IN	3.5mm stereo mini connector x 1, RCA connector L/R x 1						
AUDIO OUT	3.5mm stereo mini connector x 1						
Microphone Input	3.5mm mono mini connector x 1						
CONTROL (RS-232C)	D-sub 9-pin connector x 1						
LAN	RJ45 connector x 1						
USB-A	USB type A x 2 (PC less Presentation or wireless adapter)						
USB-B	USB type B x 1 (Interactive Function, USB mouse control and USB Display)	USB type B x 1 (USB Display and USB mouse control)					
Operating temperature	0 - 40°C						
Operating humidity (RH)	35 - 40°C (The brightness of lamp is reduced automatically.)						
Power requirements	20 - 80%RH (non-condensing)						
Maximum power consumption	AC 100-120V	AC 100-120V	AC 100-120V	AC 100-120V	AC 100-120V	AC 100-120V	
	AC 220-240V	AC 220-240V	AC 220-240V	AC 220-240V	AC 220-240V	AC 220-240V	
Standby mode power consumption	0.35W at saving mode						
Standard outside dimensions (WxHxD)	377mm x 136mm x 360mm (14.8" x 5.4" x 14.2") (Excluding protrusions)						
Weight	Approx. 4.5kg (9.9 lbs.)			Approx. 4.3kg (9.5 lbs.)			
Accessories	Remote control, AA batteries, Power cord, Computer cable, Cable cover, Adapter cover, User's manual, Security label, Application CD, USB cable, Interactive Pen, AAA batteries, Pen tips, Application DVD						
Optional parts	Lamp	DT01411	DT01511	DT01411	DT01511	DT01411	DT01511
	Filter set	UX37191					
	Mounting accessories	HAS-AW100 (Bracket for ceiling mount), HAS-203L (Fixing adaptor for low ceilings), HAS-P100 (Fixing adaptor for high ceilings), HAS-WM03 (Wall mount unit), HAS-WM05 (Wall mount unit)					
	Tabletop use kit	TT-03					
	USB wireless adapter	USB-WL-11N					
Finger Touch Unit	FT-01B						

Environment	
<ul style="list-style-type: none"> Compliance with EU Directive RoHS¹ Reduction of resin usage in production Use of hot runners in molds for making upper housing in order to reduce mill ends. Reduction of CO₂ emissions Carton volume has been cut down to 80%², reducing CO₂ emissions during transport. Power saving mode engaged during standby Eco mode Eco mode provides power saving. 	<p>¹ RoHS is the acronym of "Directive 2011/65/EU of the European Parliament and of the Council of 8 June 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment".</p> <p>² Compared to Hitachi CP-A200 ultra short throw projector on the basis of one carton box.</p>

Dimensions





Projection Distance



CP-AX3505, CP-AX3005, CP-AX2505 (1,024 x 768) (±8%)									
Screen size(diagonal)		Projection distance				Screen height			
a		b1		b2		c1		c2	
type (inch)	m	m	inch	m	inch	m	inch	m	inch
60	1.5	0.104	4.1	0.385	15.2	0.224	8.8	1.138	44.8
70	1.8	0.170	6.7	0.451	17.8	0.247	9.7	1.314	51.7
80	2.0	0.236	9.3	0.517	20.4	0.270	10.6	1.489	58.6
90	2.3	0.302	11.9	0.583	23.0	0.293	11.5	1.664	65.5
100	2.5	0.368	14.5	0.649	25.6	0.315	12.4	1.839	72.4

CP-TW3005, CP-TW2505, CP-AW3005, CP-AW2505 (1,280 x 800) (±8%)									
Screen size(diagonal)		Projection distance				Screen height			
a		b1		b2		c1		c2	
type (inch)	m	m	inch	m	inch	m	inch	m	inch
60	1.5	0.128	5.0	0.409	16.1	0.313	12.3	1.121	44.1
70	1.8	0.198	7.8	0.479	18.9	0.351	13.8	1.293	50.9
80	2.0	0.268	10.5	0.549	21.6	0.388	15.3	1.465	57.7
90	2.3	0.338	13.3	0.619	24.4	0.426	16.8	1.638	64.5
100	2.5	0.408	16.1	0.689	27.1	0.464	18.3	1.810	71.3

Terminals



- Design and specifications are subject to change without notice.
- The projected images and comparison photos in this catalog are simulations.
 - LCD panels, polarizers and other optical components and cooling fans may need replacement after prolonged usage. For more details, please consult a Hitachi sales representative.
 - Do not use in places where there is a lot of water, dampness, steam, dust, soot or tobacco smoke. This may result in fire or malfunction.
 - Optical components (lamp, LCD panel, polarizing plate, PBS [polarizer beam splitter]) have limited service lives. They must be repaired or replaced if they are used for a long period of time.
 - These projectors use a mercury lamp with high internal pressure. Because of its properties, this lamp may burst with a loud noise or burn out if struck or after it has been used for a period of time. The time until it bursts or burns out varies greatly according to differences between lamps and usage conditions. Turning the lamp's power on and off frequently shortens its service life.
 - Optical components other than the lamp: If the projector is used for six hours or more per day, they may need to be replaced in less than a year.
 - LCD panel: If the projector is used continuously for six hours or more, its replacement cycle may be shortened.
 - Do not turn projector on again for ten minutes after shutdown. Neglect can shorten the lifetime of the lamp. During use and immediately after use, do not touch anywhere near the lamp and the vents as these parts are extremely hot.
 - Windows®, Internet Explorer®, Excel® and PowerPoint® are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries.
 - Adobe, Acrobat, Flash and Reader are registered trademarks of Adobe Systems Incorporated.
 - Mac, Macintosh, Mac OS, QuickTime are registered trademarks of Apple Inc.
 - Intel, Intel Core and Pentium are trademarks of Intel Corporation in the U.S. and/or other countries.
 - Creston® and Creston RoomView® are registered trademarks of Creston Electronics, Inc. in the United States and other countries.
 - HDMI, the HDMI Logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries.
 - MHL, the MHL logo, and Mobile High-Definition Link are trademarks or registered trademarks of MHL, LLC in the United States and other countries.
 - ImageCare is a trademark or a registered trademark of Royal Philips in the United States and other countries.
 - DICOM is the registered trademark of the National Electrical Manufacturers Association for its standards publications relating to digital communications of medical information.
 - All other trademarks are the properties of their respective owners.



Ultra short throw projectors that provide vivid images in bright classrooms and meeting rooms

*Projected images are simulations

HITACHI

Hitachi America, Ltd., Digital Media Division 2420 Fenton Street, Suite 200 Chula Vista, CA 91914, U.S.A. and Canada Tel: +1-800-225-1741 www.hitachi-america.us/digitalmedia
 Hitachi Home Electronics Asia (S) Pte. Ltd. 438A Alexandra Road #01-01/02/03, Alexandra Technopark, 119967, Singapore Tel: +65-6536-2520 www.hitachiconsumer.com.sg
 Hitachi Sales (Malaysia) Sdn. Bhd. Lot 12, Jalan Kemajuan, Bangi Industrial Estate, 43650 Bandar Baru Bangi, Selangor Darul Ehsan, Malaysia Tel: +60-3-8911-2670 www.hitachiconsumer.com.my
 Hitachi Sales (Thailand), Ltd. 994, 996 Soi Thonglor, Sukhumvit 55 Road, Klongtonnu, Vadhana Bangkok 10110, Thailand Tel: +66-2335-5455 www.hitachi-th.com
 Hitachi (Hong Kong), Ltd. 18th Floor, Ever Gain Centre, 28 On Muk Street, Shatin, N.T., Hong Kong Tel: +852-2113-8883 www.hitachi-hk.com.hk
 Hitachi Sales Corp. of Taiwan 2nd Floor, No.65, Nanking East Road, Section 3, Taipei 104, Taiwan Tel: +886-2-2516-0500 www.hsct.com.tw
 Hitachi Australia Pty Ltd. Suite 801, Level 8, 123 Epping Road, North Ryde NSW 2113, Australia Tel: +61-2-9888-4100 www.hitachi.com.au
 Hitachi Europe Ltd., Digital Media Group Consumer Affairs Department Whitebrook Park, Lower Cookham Road, Maidenhead, Berkshire, SL6 8YA, UK Tel: +44-1628-585000 www.hitachidigitalmedia.com
 Hitachi Maxell, Ltd. 5030 Totsuka-cho, Totsuka-ku Yokohama, 244-0003, Japan http://www.hitachi.co.jp/proj/

January 2016

NM-E402 012016



Ultra short throw interactive projector
CP-TW3005 / CP-TW2505

Ultra short throw projector
CP-AW3005 / CP-AW2505
CP-AX3505 / CP-AX3005
CP-AX2505

Project visual beauty in real time. Technology that delivers details in bright environments.

Hitachi's original image processing technology enhances high-definition video in real time. Using this technology, you can enjoy high-definition images without losing the color information of the original image, and project high-definition video in classrooms, lecture halls, large meeting rooms, and other bright spaces.



LINE UP * Local availability may be limited.

Tseries Ultra Short Throw



Aseries Ultra Short Throw



ACCENTUALIZER


Hitachi original technology makes pictures look more real by enhancing (1) Shade, (2) Sharpness and (3) Gloss to make pictures as clear as pictures on a flat-panel device. You can also adjust the effects by three levels according to your surroundings so that the colors of projected images are the actual colors of the objects they represent.



Image Optimizer


Equipped with IMAGE OPTIMIZER, Hitachi's original function that maintains visibility of an image through automatic image correction in accordance with lamp consumption.

* This function may not work properly when HDCR/ACCENTUALIZER is ON.



HDCR (High Dynamic Contrast Range)


When average projectors are used in bright rooms, the darker colors of an image deteriorate and images become unclear. Using this function, blurred images caused by room lighting or outside light sources are corrected, and an effect similar to increasing contrast occurs. This results in clear images even in bright rooms.




DICOM® Simulation Mode

The DICOM (Digital Imaging and Communications in Medicine) Simulation Mode projects grayscale images which approximate DICOM Part 14 specifications. This mode is ideal for viewing grayscale medical images, such as X-rays, for training and educational purposes.

The projectors have a DICOM (Digital Imaging and Communications in Medicine) Simulation Mode. This mode simulates the DICOM standard, which is a standard applicable to digital communications in medicine, and is useful for displaying medical images such as X-rays. These projectors are not medical devices and are not compliant with the DICOM standard, and neither the projector nor the DICOM Simulation Mode should be used for medical diagnosis.
* Comparison photos are simulations.



* The above images are representations of the effects and differ from actual images.




Reduced Glare and Shadows

These projectors feature Ultra Short Throw, for projecting a 2m (80inches) image from only 54.9cm (21.6inches) * onto a wall or screen. Ultra Short Throw greatly reduces glare from the projector's light source, making it easier for the teacher or presenter to see the audience. The audience also has a clearer view because the shadows of the teacher's or presenter's hands and body are minimized. The result is a better classroom or meeting room experience for everyone.

* For WXGA models, 51.7cm (20.4inches) for XGA models

Powered Focus and Perfect fit

Equipped with powered focus and Perfect fit with which the position of four corners and four sides of a projected image can be adjusted. With the remote controller at hand, you can adjust focus and the position of an image.



2 - HDMI & MHL*1 inputs

Equipped with 2 HDMI input terminals for the current widely-used interface.

* HDMI cable is not included in the box.



Project images by connecting a smartphone or tablet that supports MHL to the projector using an MHL cable.

*1 For T series projectors only. MHL cable is not included in the box.



Tabletop Use (Option)



The optional tabletop use kit TT-03 allows to stand the projector vertically and a 1.5m (60")* diagonal image down onto a table.

* For WXGA models, 1.6m (63.5") for XGA models.

16W Internal Speaker

Equipped with a 16W speaker and microphone terminal that allow you to comfortably make presentations using content with sound or using a microphone.

Various Network Features

Wireless Capability (Option)

Connect a projector to a computer using the optional USB wireless adapter. The adapter supports IEEE802.11 b/g/n.

SIMPLE ACCESS POINT mode



Without an access point

INFRASTRUCTURE mode



With an access point


Easy WLAN Connection

Searches available wireless networks and displays the list of SSIDs when used in Infrastructure mode. You can select an SSID to connect to from the list.




Convenient Networking

Manage and control multiple projectors over your LAN with Centralized Reporting, Scheduling, E-mail Alerts, and My Image (Image Transfer).



Multi Projector

You can project the same image to up to 12 projectors simultaneously. This is useful for meetings and lectures in large venues where a single screen would not be sufficient.



Easy Schedule Setting

You can schedule routine and special projector events, including power on, power off, input selection and other settings.

EVENT SCHEDULE			
MONDAY to FRIDAY			
08:00	POWER	ON	
	INPUTSOURCE	COMPUTER IN 1	
12:30	INPUTSOURCE	HDMI 1	
17:00	POWER	OFF	

Smart Device Control

Plugging the optional USB wireless adapter to the projector and using the dedicated free online application developed by Hitachi, projectors can be controlled from a tablet or smartphone.




* See the Hitachi website for details http://www.hitachi.co.jp/proj/en/apps/pj_connection.html

Moderator Control Mode

Setting one computer from the multiple computers (up to 50) that are connected to the projector as the moderator (host) makes it possible for the moderator to project from all the computers (Clients).

* Moderator Control Mode supports LiveViewer 6 (Windows application) only.



Go Green


Saver Mode



This feature developed by Hitachi reduces the projector lamp brightness and consumption power, resulting in considerable energy savings. Set the Saver mode time from 1 to 30 minutes, and if the projected image does not change in that time, Saver mode activates. Saver mode can also be activated manually.



During a presentation using the screen.



Darken the screen with the remote control while the presenter speaks.




The screen automatically turns dark when not in use during group discussions.

Intelligent Eco Mode

This feature developed by Hitachi automatically changes the brightness of the lamp according to the level of the input signal. Lamp brightness is reduced when a darker image is projected, and returns to normal when a brighter image is projected, eliminating unnecessary energy consumption from the lamp.

Eco Mode

Using Eco Mode reduces lamp power approximately 32% compared to 250W¹ in Normal Mode.



Saving Mode

Consumption power can be reduced to 0.35W when in standby, making it possible to reduce running costs.

* STANDBY MODE must be set to SAVING.
* Available functions during standby when SAVING is set are limited.

Ensuring High Reliability and Stability

Easy Maintenance

The lamp door and the filter cover are located on the top and the side, facilitating maintenance and replacement even when the projector is installed on the ceiling.



Hybrid Filter


The hybrid filter is composed of an unwoven cloth and a HAF (High Air Flow) filter, protecting the optics from dust, dirt, and chalk particles. The filter can last up to 4,000 hours^{*2} without cleaning.

*2 Varies according to usage environment.



3LCD chips with Inorganic Alignment Layers

These Hitachi 3LCD projectors incorporate three LCD panels with inorganic alignment layers that are extremely light resistant, increasing brightness and contrast ratio. They ensure smooth images and high reliability.



An interactive function with enhanced operability and functionality




Advanced Writing/Drawing Capabilities

PC less Drawing

T Series projectors come with a built-in drawing function allowing you to directly draw and write on the projected screen without a PC.

Directly Draw on the Projected Screen

You can write and draw on images projected from connected devices such as Document camera.



Save and Open Drawn Screens

You can save the image drawn on the projector screen. This enables you to easily manage what you've taught in the past.

Convenient Painter Tool

Equipped with the Pen, Eraser, Undo, Redo functions. You can also change the pen color and thickness. With the easy-to-use Painter tool bar, you can teach classes smoothly.



Variety Rich Templates


You can conveniently use the interactive function with over 100 pre-installed templates including graphs, Graphic Organizers, Plain Color, and many more.



Finger Touch (Option)

The T Series projectors incorporate the optional finger touch unit that enables the projector to detect finger touch activity on the screen area. It allows users to annotate and interact with the material presented. Instead of simply showing static images, students and teachers can interact with on screen material for hands-on interactivity that brings learning to life.

* When using the finger touch unit at bright environment, auto calibration may not be used.
 * Please use the finger touch unit on a flat screen.
 * The finger touch unit may not be used in locations where there is sunlight or light from an incandescent light source.



Multiple interactive pens


With up to 6 interactive pens pupils can do more than just watch - they can interact with the onscreen content. Let them enjoy providing answers, showing their understanding and becoming involved in lessons as never before.



Windows multi touch

Windows® 8 / 8.1 multi touch allows users with touch enabled Windows® 8 / 8.1 systems to operate the PC directly from the interactive screen with up to 6 of pens or touches* including Windows® 8 / 8.1 gesture.


* Optional finger touch unit is required.



Auto Calibration

Auto calibration is completed easily and quickly with the remote control. Calibration can be performed and the interactive function can be used on both the 16 : 10 and 4 : 3 screen type.

* The image for aligning the position is displayed automatically.



Interactive Software

This product includes a drawing application that offers more sophisticated drawing functions.


Neatly Convert Letters or Figures

You can automatically convert freehand shapes into geometric objects and handwriting into text on the projected image. These operations are easily accomplished with the interactive pen.



Select a Variety of Useful Tools

The interactive pen lets you operate a compass, ruler, protractor, stopwatch and other useful tools on the projected image, making lessons even easier to understand.



System requirements for drawing application

Windows®

• **CPU:** Pentium® 4 (1.8GHz or faster) • **HDD:** 600 MB free space • **Memory:** 1 GB or more • **Display:** 32bit • **OS:** Windows® 7 (32/64bit), Windows® 8.1 (32/64bit) (The drawing application has been verified with the latest service pack at the time of release. The drawing application does not support Windows® Tablet PC Edition and Server Edition.) • **Application:** Internet Explorer® 8 / 9 / 10 / 11, Microsoft® Word 010/2013, Microsoft® Excel® 2010/2013, Microsoft® PowerPoint® 2010/2013, Adobe® Reader® X/XI, Adobe® Acrobat® Reader® DC, Adobe® Flash® Player 11 • **Others:** DVD-ROM drive, Video cards supporting hardware overlay feature. for using the movie features. [When using the Webcam function] DV (digital video devices, DV camera, D-VHS etc.), Capture Devices that supports DirectShow with WDM driver [For hosting a remote conference] • **CPU:** Intel® Core™2 Duo 2.0GHz or faster • **HDD:** 2GB or more • **Memory:** 2GB or more • **Others:** TCP/IP Network of 54Mbps or greater [For i-learn: maths toolbox] • **Display:** 1024x768 or higher • **Application:** Adobe® Reader® • **Others:** 32bit color 3D graphic card

Macintosh®

• **CPU:** Intel® CPU • **HDD:** 600 MB free space • **Memory:** 1GB or more • **Display:** High Color (16bit) or more • **OS:** Mac OS® X 10.8/10.9/10.10 • **Application:** Apple QuickTime 7.1 or later, Adobe® Flash® Player 11 • **Others:** DVD-ROM drive [For hosting a remote conference] • **CPU:** Intel® Core™2 Duo 2.0GHz or faster • **HDD:** 2GB or more • **Memory:** 2GB or more • **Others:** TCP/IP Network of 54Mbps or greater [For i-learn: maths toolbox] • **Display:** 1024 x 768 or higher • **Application:** Adobe® Reader® • **Others:** 32bit color 3D graphic card